

와일드 캠

- 전원 공급이 힘든 곳에 설치 용이
- 모션 설정으로 원하는 시간만큼의 영상 촬영 가능
- 메모리 덮어쓰기 기능



제품의 개요 (INTRODUCTION)

와일드 캠은 선로 포설이 힘든 현장에서 움직이는 영상만 촬영을 하고 싶을 때 적합한 합법적인 몰래 카메라로서 AA배터리 사용으로 어디에서든지 설치 가능.

주요 특징 (FEATURES)

- 합법적인 몰래카메라로 사용.
- 한글 메뉴 지원
- 방수 등급 개선 -IP 65
- 메모리 덮어쓰기 기능
- 고가의 설치 공사비가 들어가지 않는다.
- 사용이 간편하여 현장에서 즉시 확인이 가능.
- AA 건전지 만으로 최소 3개월 이상 사용 가능.
- 완벽한 방수로 옥외에서 사용 가능.

내부 이미지 (INSIDE IMAGE)



- ▲ (상)버튼 클릭 시 동영상모드
- ▼ (하)버튼 클릭 시 사진모드
- ▶ (우)버튼클릭 시 촬영모드

제원 및 특성 (SPECIFICATIONS)

RATING	VALUE
Image Sensor	3 Mega pixels Color CMOS
Max.Pixel	4608 x 3456
Lens	F=1.8; FOV=90°; Auto IR-Cut
IR Flash	940nm IR LED
LCD Screen	2.36 inch TFT color screen
Keypad	6 Keys, 1 Switch
Memory	TF card (8MB~32GB)
Picture Size	16MP; 12MP; 8MP; 5MP; 3MP; 1MP
Video Size	1920x1080:30fps; 1280x720:30fps; 720x480:30fps; 640x480:30fps; 320x240:30fps;
PIR Sensitivity	High / Normal / Low
PIR Sensing Distance	65ft/20m (Below 77°F/25°C at the Normal Level)
PIR Sensing Angle	60°
Operation Mode	Day/Night
Trigger Time	0.6 Second (When using the 2GB TF card)
Trigger Interval	5sec - 60 min
Shooting Numbers	1-3
Video Length	3-30sec
Camera + Video	First take Picture then Video
Playback Zoom In	1-8 Times
Time Stamp	On/Off
Time	ON/OFF; Timer Set
Password	4-Digit Numbers
Device Serial	4-Digit Numbers
Time lapse	1 Second - 24 Hours
Power Supply	4XAA; Expandable to 8xAA
Stand-by current	< 0.1 mA
Stand-by Time	4-8 Months (4xAA-8xAA)
Power Consumption	150mA (+800mA when IR LED lights up);at 6V DC
Low Battery Alarm	4.5V
Interface	USB; TF Card Slot; 6V DC External
Mounting	Belt; Tripod Nail
Waterproof	IP66
Operation Temperature	-22~+158°F/-30~+70°C
Operation Humidity	5% ~ 95%
Certificate	FC & CE & RoHS

본 제품은 성능향상을 위해 사전에 예고없이 외관 및 성능이 변경될 수 있습니다.